

The objectives of this chapter are to protect human life and health, to help maintain a stable tax base by providing for the sound use and development of Flood prone areas in such a manner as to minimize Flood blight areas, and to ensure that potential home buyers are notified that property is in a Flood area. The provisions of the chapter are intended to minimize damage to public facilities and utilities such as water and gas mains; electric, telephone, and sewer lines; streets and bridges located in the floodplain; and prolonged business interruptions. Also, an important floodplain management objective of this chapter is to minimize expenditures of public money for costly Flood control projects and rescue and relief efforts associated with flooding.

Floodplains are an important asset to the community. They perform vital natural functions such as temporary storage of floodwaters, moderation of peak Flood flows, maintenance of water quality, groundwater recharge, prevention of erosion, habitat for diverse natural wildlife populations, recreational opportunities, and aesthetic quality. These functions are best served if floodplains are kept in their natural state. Wherever possible, the natural characteristics of floodplains and their associated wetlands and water bodies should be preserved and enhanced. Decisions to alter floodplains, especially stream channels, should be the result of careful planning processes that evaluate resource conditions and human needs.

Sec. 14-4. - Lands to which this chapter applies.

This chapter shall apply to all areas of special flood hazard within the jurisdiction of the Town as identified by the Federal Emergency Management Agency (FEMA) in its Flood Insurance Study, dated December 16, 2021, as published by FEMA with accompanying flood insurance rate maps and other supporting data that are hereby adopted by reference and declared to be a part of this chapter.

Upon annexation, any special flood hazard areas identified by FEMA in its Flood Insurance Study for the unincorporated areas of Horry County, with accompanying map and other data are adopted by reference and declared part of this chapter.

Non-residential and residential Structures must be constructed so that the Lowest Floor is located no lower than the Base Flood Elevation plus three (3) feet. No environmentally conditioned space shall be allowed below the Lowest Floor. Floodproofing of commercial Structures shall not be permitted within the Town without a variance approval. Floodproofing residential Structures shall be prohibited.

This chapter shall also apply to areas outside of the SFHAs as prescribed in section 14-19.

Sec. 14-5. - Establishment of development permit.

A development permit shall be required in conformance with the provisions of this chapter prior to the commencement of any development activities.

Sec. 14-6. - Compliance.

No Structure or land shall hereafter be located, extended, converted, or structurally altered without full compliance with the terms of this chapter and other applicable regulations.

Sec. 14-7. - Interpretation.

In the interpretation and application of this chapter, all provisions shall be considered as minimum requirements, liberally construed in favor of the Town, and deemed neither to limit nor repeal any other powers granted under state law. This chapter is not intended to repeal, abrogate, or impair any existing easements, covenants, or deed restrictions. However, where this chapter and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

Sec. 14-8. - Partial invalidity and severability.

If any part of this chapter is declared invalid, the remainder of the chapter shall not be affected and shall remain in force.

Sec. 14-9. - Warning and disclaimer of liability.

The degree of Flood protection required by this chapter is considered reasonable for regulatory purposes and is based on scientific and engineering consideration. Larger Floods can and will occur on rare occasions. Flood heights may be increased by manmade or natural causes. This chapter does not

imply that land areas outside the SFHAs or uses permitted within such areas will be free from flooding or Flood damages. This chapter shall not create a liability on the part of the Town or by any officer or employee thereof for any Flood damages that result from reliance on this chapter, or any administrative decision lawfully made hereunder.

Sec. 14-10. - Penalties for violation.

Violation of the provisions of this chapter or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions, shall constitute a misdemeanor. Any person who violates this chapter or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than five hundred dollars (\$500.00) or imprisoned for not more than thirty (30) days, or both. Each day such violation continues shall be considered a separate offense. Nothing contained herein shall prevent the Town from taking such other lawful action as is necessary to prevent or remedy a violation.

Sec. 14-11. - Definition interpretation.

Unless specifically defined below, words or phrases used in this chapter shall be interpreted so as to give them the meaning they have in common usage and to give this chapter it's most reasonable application.

Sec. 14-12. - Definitions.

Accessory Structure (appurtenant structure). Structures that are located on the same parcel of property as the principal Structure and the use of which is incidental to the use of the principal Structure. Accessory Structures should constitute a minimal investment, may not be used for human habitation, and be designed to have minimal flood damage potential. Examples of Accessory Structures are detached garages, carports, storage sheds, pole barns, hay sheds, and any equipment or other decorative fixtures affixed to the property.

Accessory Use. A subordinate use which is incidental to and customary in connection with the principal Structure or use and which is located on the same lot with such principal Structure or use.

Addition (to an existing Structure). An extension or increase in the floor area or height of a Structure. Additions to existing Structures shall comply with the requirements for New Construction regardless whether the Addition is a Substantial Improvement or not. Where a firewall or load-bearing wall is provided between the Addition and the existing Structure, the Addition(s) shall be considered a separate Structure and must comply with the standards for New Construction. All decks and porches shall be considered Additions.

Agricultural Structure. A Structure used solely for agricultural purposes in which the use is exclusively in connection with the production, harvesting, storage, drying, or raising of agricultural commodities, including the raising of livestock. Agricultural Structures are not exempt from the provisions of this chapter.

Appeal. A request for a review of the local floodplain administrator's interpretation of any provision of this chapter.

Base Flood or Base Flood Elevation (BFE). The Flood having a one percent (1%) chance of being equaled or exceeded in any given year.

Basement. Any enclosed area of a Structure which is below grade on all sides.

Coastal High Hazard Area. A SFHA extending from offshore to the inland limit of the primary frontal dune along an open coast and any other area subject to velocity wave action from storms or seismic sources and designated as VE Zone.

Coastal A Zone. Area landward of a VE Zone where the principal source of flooding will be astronomical tides, storm surges or tsunamis, not riverine flooding. During Base Flood conditions, the potential for breaking wave heights between 1.5 feet and 3.0 feet will exist..

Critical Facilities. Facilities that are critical to the community's public health and safety, are essential to the orderly functioning of a community; used to store or produce highly volatile, toxic or water-reactive

materials; or house occupants that may be insufficiently mobile to avoid loss of life or injury. Examples of Critical Facilities include jails, hospitals, schools, fire stations, nursing homes, wastewater treatment facilities, water plants, and gas/oil/propane storage facilities.

Development. Any manmade change to improved or unimproved real estate, including, but not limited to, Structures, Additions, improvements, mining, dredging, filling, grading, paving, excavation or drilling operations, or storage of equipment or materials.

Elevated Building - a non-Basement Structure built to have the Lowest Floor elevated above the ground level by means of fill, solid foundation perimeter walls, pilings, columns, piers, or shear walls parallel to the flow of water.

Executive Order 11988 (Floodplain Management). Issued by President Carter in 1977, this order requires that no federally assisted activities be conducted in or have the potential to affect identified SFHAs, unless there is no practicable alternative.

[Note – moved for alphabetical order] Existing Construction. For the purposes of determining rates, Structures for which the Start of Construction commenced before December 17, 1976.

Existing Manufactured Home Park or Manufactured Home subdivision. A Manufactured Home Park or subdivision for which the construction of facilities for servicing the lots on which the Manufactured Homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, and either final site-grading or the pouring of concrete pads) is completed before February 5, 1980.

Flood. A general and temporary condition of partial or complete inundation of normally dry land areas from the overflow of inland or tidal waters, or the unusual and rapid accumulation of runoff of surface waters from any source.

Flood Hazard Boundary Map (FHBM). An official map of a community issued by FEMA, where the boundaries of the areas of flood hazard have been defined as Zone A.

Flood Insurance Rate Map (FIRM). An official map of a community, on which FEMA has delineated both the SFHAs and the risk premium zones applicable to the community.

Flood Insurance Study. The official report provided by FEMA. The report contains Flood profiles, as well as the FHBM and the water surface elevation of the Base Flood.

Flood-Resistant Material. Any building material capable of withstanding direct and prolonged contact (minimum seventy-two (72) hours) with floodwaters without sustaining damage that requires more than low-cost cosmetic repair. Any material that is not water soluble or is not resistant to alkali or acid in water, including normal adhesives for above-grade use, is not Flood-Resistant Material. Pressure-treated lumber or naturally decay-resistant lumber are acceptable flooring materials. Sheet-type floor coverings that restrict evaporation from below and materials that are impervious, but dimensionally unstable are not acceptable. Materials that absorb or retain water excessively after submergence are not Flood-Resistant Materials. Please refer to Technical Bulletin 2, *Flood Damage-Resistant Materials Requirements*, dated 8/08, and available from FEMA. Class 4 and 5 materials, referenced therein, are acceptable Flood-Resistant Materials.

Flood Vent. A permanent opening in a wall that allows the free passage of water automatically in both directions without human intervention.

Freeboard. A factor of safety usually expressed in feet above a Flood level for purposes of floodplain management. Freeboard tends to compensate for the many unknown factors that could contribute to Flood heights greater than the height calculated for a selected size Flood conditions, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed.

Functionally Dependent Use. A use that cannot perform its intended purpose unless it is located or carried out in close proximity to water such as a fishing pier, docking or port facility necessary for the loading and unloading of cargo or passengers, shipbuilding, ship repair facilities, or seafood processing facilities. The term does not include long term storage, manufacturing, sales, or service facilities.

Highest Adjacent Grade. The highest natural elevation, as certified by a registered land surveyor, engineer or architect, of the ground surface next to the proposed exterior walls of a Structure.

Historic Structure. Any Structure that is:

- (a) Listed individually in the National Register of Historic Places (a listing maintained by the U.S. Department of the Interior (DOI) or preliminary determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- (b) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary of the Interior to qualify as a registered historic district;
- (c) Individually listed on a state inventory of historic places; and
- (d) Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified:
 - (1) By an approved state program as determined by the Secretary of the Interior; or
 - (2) Directly by the Secretary of the Interior in states without approved programs.

Some Structures or districts listed on the state or local inventories may not be "historic" as cited above, but have been included on the inventories because it was believed that the Structures or districts have the potential for meeting the Historic Structure criteria of the DOI. In order for these Structures to meet NFIP Historic Structure criteria, it must be demonstrated and evidenced that the South Carolina Department of Archives and History has individually determined that the Structure or district meets DOI Historic Structure criteria.

Increased Cost of Compliance (ICC). The National Flood Insurance Program (NFIP) shall enable the purchase of insurance to cover the cost of compliance with land use and control measures established under Section 1361 of the National Flood Insurance Act. It provides coverage for the payment of a claim to help pay for the cost to comply with State or community floodplain management laws or ordinances after a Flood event in which a Structure has been declared substantially or repetitively damaged. Increased Cost of Compliance applies to all new and renewed Flood insurance policies effective on and after June 1, 1997.

Limited Storage (enclosures). An area used for storage and intended to be limited to incidental items that can withstand exposure to the elements and have low Flood damage potential. Such an area must be of Flood-Resistant Material or breakaway material, void of utilities except for essential lighting and cannot be temperature controlled. If the area is located below the Base Flood Elevation in an A, AE and A1-A30 zones, it must meet the requirements of subsection 14-18(4)(b) of this chapter. No storage or enclosures shall be permitted below the Base Flood Elevation in a VE and Coastal A zone.

Lowest Adjacent Grade (LAG). An elevation of the lowest ground surface that touches any deck support, exterior walls of a Structure or proposed Structure walls.

Lowest Floor. The lowest enclosed area (including Basement). Any unfinished or Flood-resistant enclosure, usable solely for parking of vehicles, building access, or storage in an area other than a Basement area, is not considered a Structure's Lowest Floor, provided such an enclosure is not built so as to render the Structure in violation of other provisions of this chapter.

Manufactured Home. A Structure, transportable in one (1) or more sections, that is built to HUD standards on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term Manufactured Home does not include a Recreational Vehicle or a South Carolina Building Code Council approved modular home.

Manufactured Home Park or subdivisions. A parcel (or contiguous parcels) of land divided into two (2) or more Manufactured Home lots for rent or sale.

Mean Sea Level. For the purpose of this chapter, the Nations Geodetic Vertical Datum (NGVD) of 1929, North American Vertical Datum (NAVD) of 1988, or other datum, to which the Base Flood Elevations shown on a community's FIRMs are shown.

National Geodetic Vertical Datum (NGVD). As corrected in 1929, elevation reference points set by National Geodetic Survey based on Mean Sea Level.

North American Vertical Datum (NAVD) of 1988. Vertical control, as corrected in 1988, used as the reference datum on FIRMs.

North American Vertical Datum (NAVD). Datum point established at Pointe-au-Pere on the St. Lawrence River, Quebec Province, Canada, based on the mass or density of the earth. The datum listed as the reference datum on FIRMs should be used for elevation certificate completion.

New Construction. Structure for which the start of the construction commenced on or after February 5, 1980. The term also includes any subsequent improvements to such a Structure.

Non-conversion agreement. An agreement signed by the property owner as a condition of a certificate of occupancy. The owner must agree to not alter the Structure at a later date so as to violate the building code or the requirements of this chapter. The Non-conversion agreement shall be binding upon heirs, grantees, successors and assigns of parties hereto and shall constitute a covenant running with the Structure being constructed under said certificate. The Non-conversion agreement shall be recorded in the Horry County Register of Deeds prior to obtaining a certificate of occupancy inspection.

[Note – moved for alphabetical order.] Primary Frontal Dune. A continuous or nearly continuous mound or ridge of sand with relatively steep seaward and landward slopes and subject to erosion and overtopping from high tides and waves during coastal storms. The inland limit of the Primary Frontal Dune occurs at the point where there is a distinct change from relatively steep slope to a relatively mild slope.

Recreational Vehicle. A vehicle which is:

- (a) Built on a single chassis;
- (b) Four hundred (400) square feet or less when measured at the largest horizontal projection;
- (c) Designed to be self-propelled or permanently towable by a light duty truck; and
- (d) Designed primarily not for use as a permanent dwelling, but as temporary living quarters for recreation, camping, travel, or seasonal use.

Repetitive Loss. A Structure covered by a contract for Flood insurance that has incurred Flood-related damages on two (2) occasions during a 10-year period ending on the date of the event for which a second claim is made, in which the cost of repairing the Flood damage, on the average, equaled or exceeded twenty-five (25%) of the market value of the Structure at the time of each such Flood event.

Section 1316 of the National Flood Insurance Act of 1968. The act provides that no new Flood insurance shall be provided for any property found by FEMA to have been declared by a state or local authority to be in violation of state or local ordinances.

Stable Natural Vegetation. The first place on the oceanfront where plants such as sea oats hold sand in place.

Special Flood Hazard Area (SFHA). The area that will be inundated by the Flood event having a one percent (1%) chance of being equaled or exceeded in any given year. The one percent (1%) annual chance Flood is also referred to as the Base Flood or 100-year flood. SFHAs are labeled as zone AE, VE, and Coastal A.

Start of Construction. For other than New Construction or Substantial Improvements under the Coastal Barrier Resources Act (P.L. 97-348), the date the building permit was issued, provided the actual Start of Construction, repair, reconstruction, rehabilitation, Addition, or improvement was within one hundred eighty (180) days of the permit date. The actual Start of Construction means the first placement of permanent construction of a Structure (including a Manufactured Home) on a site, such as the pouring of slabs or footings, installation of piles, construction of columns, or any work beyond the stage of excavation or the placement of a Manufactured Home on a foundation. Permanent construction does not include land preparation, such as clearing, grading, and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for footings, piers or foundations, or the erection of temporary forms; nor does it include the installation on the property of Accessory Structures, such as garages or sheds not occupied as dwelling units and not part of the main Structure. For Substantial Improvement, the actual Start of the Construction means the first alteration of any wall, ceiling, floor, or

other structural part of the Structure, whether or not that alteration affects the external dimensions of the Structure.

Structure. A walled and roofed building or a Manufactured Home, including any gas or liquid storage tank(s) that is principally above ground and any Accessory Structures.

Substantial Damage. Damage of any origin sustained by a Structure whereby the cost of restoring the Structure to it's before damaged conditions would equal or exceed forty-eight percent (48%) of the market value of the Structure before the damage occurred. Such repairs may be undertaken successively and their costs counted cumulatively. Refer to the definition of Substantial Improvement.

Substantial Improvement. Any repair, reconstruction, rehabilitation, Addition, or other improvement of a Structure, the cost of which equals or exceeds forty-eight percent (48%) of the market value of the Structure before the Start of Construction of the improvement. This term includes Structures that have incurred Repetitive Loss or Substantial Damage, regardless of the actual repair work performed. The term does not, however, include either:

- (1) Any project of improvement to a Structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to ensure safe living conditions or,
- (2) Any alteration of a Historic Structure, provided that the alteration will not preclude the structure's continued designation as a Historic Structure.

Permits shall be cumulative for a period of five (5) years. If the improvement project is conducted in phases, the total of all costs associated with each phase, beginning with the issuance of the first permit, shall be utilized to determine whether "Substantial Improvement" will occur.

Substantially Improved Existing Manufactured Home Park or subdivision - where the repair, reconstruction, rehabilitation or improvement of the streets, utilities and pads equals or exceeds forty-eight percent (48%) of the value of the streets, utilities and pads before the repair, reconstruction, or improvement commenced.

Variance. The grant of relief from a term or terms of this chapter.

Violation. The failure of a Structure or other development to be fully compliant with these regulations.

Sec. 14-13. - Designation of local floodplain administrator.

The building and codes director or their designee is hereby designated as the local floodplain administrator appointed to administer and implement the provisions of this chapter.

Sec. 14-14. - Development permit and certification requirements.

Application for a Development permit shall be made to the local floodplain administrator on forms furnished by the Town prior to any development activities. The development permit may require, but not be limited to, plans in duplicate drawn to scale showing: the nature, location, dimensions, and elevations of the area in question; existing or proposed Structures; and the location of storage areas, and drainage facilities. Specifically the following information is required:

- (1) A certified survey providing the following information:
 - a. Scale and north orientation arrow;
 - b. Parcel boundaries and the location and names of adjacent streets;
 - c. All watercourses on the parcel;
 - d. All floodplain, AE, VE, or Coastal A-zone that run through the parcel certified by a registered land surveyor or professional engineer with the FIRM number and date the map was enacted;
 - e. Flood boundaries/zones must be certified accurate with latest adopted Flood map information included;

- f. All required buffer or setback lines from shoreline or channel banks;
 - g. All drainage and utility easements;
 - h. All areas to be cleared, cut or graded;
 - i. The location of existing and proposed fences, walls and other Structures;
 - j. The 100-year floodplain contour or a statement certifying that the entire lot is within the floodplain must be provided by the development permit applicant when the lot is within or appears to be within the floodplain as mapped by FEMA or the floodplain identified pursuant to either section 14-15(9) or section 14-18.
- (2) The survey must be prepared by or under the direct supervision of a registered land surveyor or professional engineer and certified by same.
 - (3) If the permit includes a new Structure or an expansion of an existing Structure the survey must show the footprint of all existing and proposed Structures and Additions.
 - (4) As a condition of receiving a Development permit, a complete stormwater plan with narrative as set forth in Article III - Stormwater Management hereof shall be submitted and approved. This requirement shall apply to all parcels within the Town limits.
 - (5) Where Base Flood Elevation data is provided as set forth in section 14-4 or section 14-15(9), the application for a development permit within the Flood hazard area shall include an elevation certificate showing the elevation (in relation to Mean Sea Level) of the Lowest Floor of all New Construction, Additions and Substantially Improved Structures.
 - (6) Where any watercourse will be altered or relocated as a result of proposed project, the application for a Development permit shall include: a description of the extent of watercourse alteration or relocation; an engineering report on the effects of the proposed project on the Flood-carrying capacity of the altered or relocated watercourse; the effects to properties located both upstream and downstream; and a map showing the location of the proposed watercourse alteration or relocation.
 - (7) An elevation certificate providing floor elevation is required after the Lowest Floor is completed. As soon as possible after completion of the Lowest Floor and before any further vertical construction commences, it shall be the duty of the permit holder to submit to the local floodplain administrator a certification of the Lowest Floor, as built, in relation to Mean Sea Level. Said certification shall be prepared by or under the direct supervision of a registered land surveyor or professional engineer and certified by the same. Any work done prior to submission of the certification shall be at the permit holder's risk. The local floodplain administrator shall review the floor elevation survey data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to any additional work being permitted to proceed. Failure to submit the survey or failure to make said corrections required shall be cause to issue a stop work order for the project.
 - (8) In Coastal High Hazard Areas (VE, or Coastal A zone), documentation from a professional engineer must be acquired stating the slab placed under the Structure is not connected to the foundation.
 - (9) When a Structure is located in zones VE, or Coastal A zone certification shall be provided from a registered professional engineer or architect, separate from submitted plans, that New Construction, Additions or Substantial Improvement meets the criteria in section 14-22(5).
 - (10) Upon completion of the development, a registered professional engineer, land surveyor or architect, whichever professional is appropriate in accordance with state law, shall certify by elevation certificate and any other documentation required that subsection 14-14(7), (8), and (9) is built in accordance with the submitted plans and previous predevelopment certifications.
 - (11) A Non-conversion agreement shall be required on all Structures within the SFHA when the Structure is completed and the owner applies for a certificate of occupancy or a use permit. This is done after the final inspection, when the Town confirms that the Structure meets all building

codes and the requirements of this chapter. The agreement must be recorded in the Horry County Register of Deeds office and a clocked copy must be returned to the Town to be filed with the building and codes department prior to a certificate of occupancy inspection being made. This requirement includes but is not limited to New Construction, Additions, Substantial Improvements and renovations.

- (12) If the proposed project will impact the configuration of a watercourse, or Base Flood Elevation for which a detailed Flood Insurance Study has been developed, the applicant shall apply for and must receive approval for a conditional letter of map revision with FEMA prior to actual construction.

Sec. 14-15. - Duties and responsibilities of the local floodplain administrator.

Duties of the local floodplain administrator shall include, but not be limited to:

- (1) *Permit Review.* Review all Development permits to ensure that the requirements of this chapter have been satisfied.
- (2) *Requirements of federal and/or state permits.* Review proposed Development to ensure that all necessary permits have been received from those governmental agencies from which approval is required by federal or state law, including section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C 1334.
- (3) *Watercourse alterations.*
 - a. Notify adjacent communities and the South Carolina Department of Natural Resources, Land, Water, and Conservation Division, State Coordinator for the National Flood Insurance Program, prior to any alteration or relocation of a watercourse, and submit evidence of such notification to FEMA.
 - b. In addition to the notifications required watercourse alterations per section 14-15(3)(a), written reports of maintenance records must be maintained to show that maintenance has been provided within the altered or relocated portion of said watercourse so that the Flood-carrying capacity is maintained. This maintenance must consist of a comprehensive program of periodic inspections, and routine channel clearing and dredging, or other related functions. The reports shall consist of a description of maintenance activities, frequency of performance, and the local official responsible for maintenance performance. Records shall be kept on file for FEMA inspection.
 - c. If the proposed project will modify the configuration of the watercourse, floodway, or base flood elevation for which a detailed flood insurance study has been developed, the applicant shall apply for and must receive approval for a conditional letter of map revision with the Federal Emergency Management Agency prior to the start of construction.

Within sixty (60) days of completion of an alteration of a watercourse, referenced in the certification requirements of section 14-14(6) the applicant shall submit as-built certification, by a registered professional engineer, to FEMA.

- (4) The local floodplain administrator must ensure that a registered professional engineer shall certify that the design, specifications and plans for construction are in compliance with the provisions contained in subsections 14-22(6) and (15) of this chapter.
- (5) *Adjoining floodplains.* Cooperate with neighboring communities with respect to the management of adjoining floodplains and/or Flood-related erosion areas to prevent aggravation of existing hazards.
- (6) Notify adjacent communities prior to permitting substantial commercial developments and large subdivisions to be undertaken in SFHAs and/or area affected by Flood-related erosion hazards.
- (7) Where interpretation is needed as to the exact location of boundaries of the SFHAs (for example, where there appears to be a conflict between a mapped boundary and actual field conditions), the local floodplain administrator shall make the necessary interpretation. The

person contesting the location of the boundary shall be given a reasonable opportunity to Appeal the interpretations as provided in this article.

- (8) When Base Flood Elevation data has not been provided in accordance with section 14-4, obtain, review, and reasonably utilize best Base Flood Elevation data available from a federal, state, or other source, including data developed pursuant to section 14-20, in order to administer the provisions of this chapter. Data from preliminary, draft and the final Flood Insurance Studies constitutes best available data from a federal, state, or other source. If an Appeal is pending on the study in accordance with 44 CFR Ch. 1, Parts 67.5 and 67.6, the data does not have to be used.
- (9) When the exact location of boundaries of the SFHAs conflict with the current natural topography information at the site, the site information takes precedence when the Lowest Adjacent Grade is at or above the BFE, and the property owner may apply and be approved for a letter of map amendment (LOMA) by FEMA. A copy of the letter of map amendment issued from FEMA will be maintained by the local floodplain administrator in the permit file.
- (10) *Prevailing Authority* - Where a map boundary showing a SFHA and field elevations disagree, the Base Flood Elevations for Flood protection elevations (as found on an elevation profile, ~~Floodway data table~~, etc.) shall prevail.
- (11) Make on-site inspections of projects in accordance with section 14-16(1).
- (12) Serve notices of violations, issue stop work orders, revoke permits, and take corrective actions in accordance with section 14-16.
- (13) Maintain all records pertaining to the administration of this chapter and make these records available for public inspection.
- (14) *Annexations or detachments*. Notify the South Carolina Department of Natural Resources, Land and Conservation Division, State Coordinator for the National Flood Insurance Program within six (6) months, of any annexations or detachments that include SFHAs. The community must incorporate applicable maps from surrounding jurisdictions into this chapter within ninety (90) days of annexation or detachment.
- (15) *Federally funded development*. The President issued Executive Order 11988, Floodplain Management May 1977. E.O. 11988 directs federal agencies to assert a leadership role in reducing Flood losses and losses to environmental values served by floodplains. Proposed Developments must go through an eight-step review process. Evidence of compliance with the executive order must be submitted as part of the permit review process.
- (16) *Substantial Damage determination*. Perform an assessment of damage from any origin to the Structure to determine if the damage equals or exceeds forty-eight percent (48%) of the market value of the Structure before the damage occurred.
- (17) *Substantial Improvement determinations*. Perform an assessment of permit applications for improvements or repairs to be made to a Structure that equals or exceeds forty-eight percent (48%) of the market value of the Structure before the Start of Construction. Cost of work counted for determining if and when Substantial Improvement to a Structure occurs shall be cumulative for a period of five (5) years. If the improvement project is conducted in phases, the total of all costs associated with each phase, beginning with the issuance of the first permit, shall be utilized to determine whether Substantial Improvement will occur.

The market values shall be determined by one of the following methods:

- a. The current assessed Structure value as determined by the county's assessor's office or the value of an appraisal performed by a licensed appraiser at the expense of the owner within the past six (6) months.
- b. One or more certified appraisals from a registered professional licensed appraiser in accordance with the laws of South Carolina. The appraisal shall indicate actual

replacement value of the Structure in its pre-improvement condition, less the cost of site improvements and depreciation for functionality and obsolescence.

- c. Real estate purchase contract within six (6) months prior to the date of the application for a permit.

Sec. 14-16. - Administrative procedures.

- (1) *Inspections of work in progress.* As the work pursuant to a permit progresses, the local floodplain administrator or their designee shall make as many inspections of the work as may be necessary to ensure that the work is being done according to the provisions of this chapter and the terms of the permit. A minimum of three (3) inspections shall be performed for each permitted development project in the regulated floodplain:

The first inspection is conducted when the site is staked out or otherwise marked and a "construction drawings" elevation certification is provided to the Town. The inspector checks that areas subject to special requirements are clearly marked on the ground.

The second inspection is conducted when the Lowest Floor is built for a Structure or Addition. The builder provides the Town with documentation of the surveyed Lowest Floor elevation ("building under construction" elevation certificate). The inspector checks that:

- a. The foundation or forms for the Structure are correctly located on the site;
- b. Where Structures have enclosures below the Base Flood Elevation (permitted in AE zones only), the location and size of the openings are as specified on the approved plans; and
- c. In Coastal High Hazard Areas (VE, or Coastal A zones), slabs placed under the Structure are not connected to the foundation.

The third inspection is conducted when the project is finished; the "finished construction" elevation certificate is submitted, and before the final inspection. The inspector checks:

- a. The foundation and floor elevation have not been altered since the second inspection;
 - b. All areas below the required elevation are constructed with Flood-Resistant Materials and do not exceed the allowed square footage. For those Structures in the VE, and Coastal A Zones, no areas are enclosed below the required elevation;
 - c. Where Structures have enclosures below the Base Flood Elevation (permitted in AE zones only), the location and size of the openings are specified on the approved plans and recorded on the elevation certificate.
 - d. All electrical, heating, ventilation, plumbing, air conditioning, ductwork, and other equipment is located, elevated, or protected as specified on the approved plans and recorded on the elevation certificate.
 - e. There has been no alteration of the ground since the second inspection or the ground has been graded according to the approved plans.
- (2) *Stop work orders.* Whenever a Structure or part thereof is being constructed, reconstructed, altered, or repaired in violation of this chapter, the local floodplain administrator or their designee may order the work to immediately be stopped. The stop work order shall be in writing and directed to the person doing the work. Notification of the property owner is also required. The stop work order shall state the specific work to be stopped, the specific reasons for the stoppage, and the conditions under which the work may be resumed. Violation of a stop work order shall constitute a misdemeanor.
 - (3) *Revocation of permits.* The local floodplain administrator may revoke and require the return of the Development permit by notifying the permit holder and owner in writing, stating the reason for the revocation. Permits shall be revoked for any substantial departure from the approved application, plans, or specifications; for refusal or failure to comply with the requirements of state or local laws; or for false statements or misrepresentations made in securing the permit. Any permit mistakenly issued in violation of an applicable state or local law shall also be revoked.

- (4) *Periodic inspections.* The local floodplain administrator and each member of the inspection department shall have a right, upon presentation of proper credentials, to enter on any premises within the territorial jurisdiction of the department at any reasonable hour for the purposes of inspection or other enforcement action.
- (5) *Violations to be corrected.* When the local floodplain administrator finds violations of applicable state and local laws, it shall be their duty to notify the owner or occupant of the building of the violation. The owner shall immediately remedy each of the violations of law on the property they own.
- (6) *Actions in event of failure to take corrective action.* If the owner of a Structure or property shall fail to take prompt corrective action, the local floodplain administrator shall give them written notice, by certified or registered mail to the last known address or by personal service, that:
 - a. The Structure or property is in violation of this chapter;
 - b. A hearing will be held before the local floodplain administrator at a designated place and time, not later than ten (10) days after the date of notice, at which time the owner shall be entitled to be heard in person or by counsel and to present arguments and evidence pertaining to the matter; and
 - c. Following the hearing, the local floodplain administrator may issue such order to alter, vacate, or demolish the Structure, or to remove fill as appears appropriate.
- (7) *Order to take corrective action.* If, upon a hearing held pursuant to the notice prescribed above, the local floodplain administrator shall find that the Structure or Development is in violation of this chapter, they shall make such an order in writing to the owner, requiring the owner to remedy the violation within such period, not more than sixty (60) days, the local floodplain administrator may prescribe; provided that where the local floodplain administrator finds that there is imminent danger to life or other property, that corrective action be taken in such lesser period that may be feasible.
- (8) *Appeal.* Any owner who has received an order to take corrective action may Appeal the order to the Town's Construction Board of Appeals by giving notice of Appeal in writing to the local floodplain administrator and the Town Clerk within ten (10) days following issuance of the final order. In the absence of an Appeal, the order of the local floodplain administrator shall be final. The Construction Board of Appeals shall hear an Appeal within a reasonable time and may affirm, modify, or revoke the order.
- (9) *Failure to comply with order.* If the owner of a Structure or property fails to comply with an order to take corrective action from which no Appeal has been taken, or fails to comply with an order of the Construction Board of Appeals following an Appeal, they shall be guilty of a misdemeanor and shall be punished in the discretion of the court.
- (10) *Denial of flood insurance under the NFIP.* If a Structure is declared in violation of this chapter and after all other recourses are exhausted to achieve compliance with this chapter then the local floodplain administrator shall notify FEMA to initiate a Section 1316 of the National Flood Insurance Act of 1968 action against the Structure upon the finding that the violator refuses to bring the violation into compliance with this chapter. Once a violation has been remedied the local floodplain administrator shall notify FEMA of the remedy and ask that the Section 1316 action be rescinded.
- (11) The following documents are incorporated by reference and may be used by the local floodplain administrator to provide further guidance and interpretation of this chapter as found on FEMA's website at www.fema.gov :
 - a. FEMA 55 Coastal Construction Manual.
 - b. All FEMA Technical Bulletins.
 - c. All FEMA Floodplain Management Bulletins.
 - d. FEMA 348 Protecting Building Utilities from Flood Damage.
 - e. FEMA 499 Home Builder's Guide to Coastal Construction Technical Fact Sheets.

Sec. 14-17. - Flood hazard reduction standards.

Development may not occur in the SFHAs where alternative locations exist due to inherent hazards and risks involved. Before a permit is issued, the applicant shall demonstrate that new Structures (and Additions) cannot be located out of the SFHA and that encroachments onto the SHFA are minimized. In all SFHAs, the following provisions are required:

- (1) *Reasonably safe from flooding.* Review all permit applications to determine whether proposed building sites will be reasonably safe from flooding.
- (2) *Anchoring.* All New Construction, Additions and/or Substantial Improvements shall be anchored to prevent flotation, collapse, or lateral movement of the structure;
- (3) *Flood Resistant Materials and Equipment -* All New Construction, Additions and Substantial Improvements shall be constructed with Flood-Resistant Materials and utility equipment resistant to Flood damage in accordance with Technical Bulletin 2, Flood Damage-Resistant Materials Requirements, dated 8/08, and available from FEMA.
- (4) *Minimize Flood Damage.* All new construction, additions and/or substantial improvements shall be constructed by methods and practices that minimize Flood damages;
- (5) *Utilities.* Electrical, ventilation, plumbing, heating and air conditioning equipment (including ductwork), and other service facilities shall be designed and/or located at least three (3) feet above the required Base Flood Elevation so as to prevent water from entering or accumulating within or on the components during conditions of Flooding. This requirement does not preclude the installation of outdoor faucets for shower heads, hoses, etc., as long as cutoff devices and backflow devices are installed to prevent contamination of the service components and thereby minimize any Flood damages to a Structure and contents;
- (6) *Gas or Liquid Storage Tanks –* All gas containers shall be anchored to prevent flotation, collapse, or lateral movement resulting from hydrodynamic or hydrostatic loads. Horizontal propane tanks shall install four (4) ground anchors connected across the top of the tank with metal straps. Vertical propane tanks shall be installed with two (2) ground anchors, each anchor placed on opposite sides of the vertical tank. A strap shall be attached from each anchor to the collar secured around the top of the tank. An additional metal strap shall be connected from one anchor to the other through the tank base. Ground anchors, straps, and connecting hardware must be corrosion - resistant.
- (7) Non-commercial developable lots located in the X, X shaded and AE zones shall have an average grade of all adjacent lots. A foundation/current conditions survey shall be provided and approved prior to the foundation being poured or piers being filled, and prior to additional inspections being performed. Adjacent lot grades shall be measured at a minimum of twenty (20) feet into all adjacent lots. This requirement shall not apply to designated Coastal A and VE zones as no fill shall be allowed for structural support in these SFHAs. Only non-compacted fill may be used around the perimeter of a Structure for landscaping/aesthetic purposes provided the fill will wash out from storm surge, thereby rendering the Structure free of obstruction prior to generating excessive loading forces, ramping effects, or wave deflection. See section 14-22(6) for complete requirements.
- (8) *Water Supply Systems.* All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the system;
- (9) New and replacement sanitary sewer shall be designed to minimize or eliminate infiltration of floodwaters into the system and discharges from the systems into floodwaters;
- (10) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding; and
- (11) *Alteration, Repair, Reconstruction, or Improvements.* Any alteration, repair, reconstruction, Addition or improvement to a Structure which is in compliance with the provisions of this

chapter, shall meet the requirements of New Construction as contained in this chapter. This includes post-FIRM Development and Structures.

- (12) *Nonconforming structures or uses.* Nonconforming Structures or uses may not be enlarged, replaced, or rebuilt unless such enlargement or reconstruction is accomplished in conformance with the provisions of this chapter. Use of nonconforming ground floor habitable spaces or walls for an Addition of a second floor above the Base Flood Elevation shall not be allowed.
- (13) *Americans with Disabilities Act (ADA).* A Structure must meet the specific standards for floodplain construction outlined in section 14-18, as well as any applicable ADA requirements. The ADA is not justification for issuing a variance or otherwise waiving the requirements of this chapter. Also, the cost of improvements required to meet the ADA provisions shall be included in calculating Substantial Improvement.
- (14) All New Construction, Additions and/or Substantial Improvements shall be designed and sealed by a registered design professional as complying with the requirements of the latest adopted International Building Code or International Residential Code, whichever is applicable.
- (15) Slab construction (including raised slabs) shall be prohibited within all SFHAs.
- (16) Flood proofing or wet-proofing of commercial Structures as a Flood protection measure shall be prohibited without a variance approval. All Structures (including non-residential) shall be required to elevate to the Base Flood Elevation plus three (3) feet. Floodproofing of residential Structures shall be prohibited.
- (17) New septic systems in floodplains are prohibited.
- (18) *Critical facilities.* Critical Facilities as defined in section 14-12 shall be prohibited in the 500-year flood zone. (Note: The 500-year floodplain includes the entire SFHA plus other land that is lower than the 500-year Flood elevation).
- (19) *Hazardous velocities.* Hydrodynamic pressure must be considered in the design of any foundation system where velocity waters or the potential for debris flow exists. Therefore, solid foundation walls shall not be permitted within any SFHA.
- (20) All fences crossing floodplain boundaries are subject to Flood review. The most restrictive zone crossed by the fence will prevail. All fencing material shall be Flood-Resistant Materials.
- (21) There shall be no alteration of sand dunes which would increase potential Flood damage.
- (22) Swimming pools in a SFHA: Pools located within the SFHA shall be built to the following standards:
 - a. Swimming pools must meet all applicable requirements set forth in the zoning ordinance.
 - b. Swimming pools must be sited as far away from the regulatory Flood boundary as feasible.
 - c. No above grade pools are allowed in the VE or Coastal A zone.
 - d. No portion of a swimming pool in the VE or Coastal A zones shall be allowed more than six (6) inches above the adjacent grade.
 - e. Swimming pools beneath a Structure in any SFHA must be flush with the natural grade and must be engineered certifying:
 - i. The swimming pool or other obstruction will not be subject to breaking up or flooding out the ground and affecting the piles or columns of the Structure; and
 - ii. The swimming pool shall meet the same anchoring requirements as the support system of the Structure.
 - f. Enclosures associated with any swimming pool located in the SFHA shall not be permitted in the VE or Coastal A zone.
- (23) Recreational Vehicles shall not be permitted within the SFHA.

- (24) Outdoor storage of any kind shall be prohibited within the SFHA.
- (25) No Basements shall be permitted within the Town limits.

Sec. 14-18. - Specific standards.

In all areas of flood hazard (AE zones) where Base Flood Elevation data has been provided, as set forth in section 14-4 the following provisions are required in addition to those set forth in section 14-17 of this chapter:

- (1) *Residential construction.* New Construction, Addition and Substantial Improvement of any residential Structure (including Manufactured Homes) shall have the Lowest Floor elevated not lower than three (3) feet above the Base Flood Elevation. No Basements are permitted.
- (2) *Non-residential construction.*
 - a. New Construction, Addition and Substantial Improvement of any commercial, industrial, or non-residential Structure (including manufactured structures) shall have the Lowest Floor elevated no lower than three (3) feet above the level of the Base Flood Elevation. No Basements are permitted.
 - b. A registered professional engineer or architect shall certify that the standards of this section 14-18(2) are satisfied. Agricultural structures not meeting the criteria of section 14-27 must meet the non-residential construction standards and all other applicable provisions of this chapter.
- (3) *Manufactured homes.*
 - a. No new Manufactured Homes shall be permitted, except in an Existing Manufactured Home Park or subdivision. A replacement Manufactured Home may be placed on a lot in an Existing Manufactured Home Park or subdivision, provided the anchoring and the elevation standards of subsection 14-18(3)(c) are met.
 - b. Manufactured Homes that are placed or Substantially Improved on sites in an Existing Manufactured Home Park or subdivision on which as Manufactured Home has incurred Substantial Damage as a result of a Flood, must be elevated on a permanent foundation such that the Lowest Floor of the Manufactured Home is elevated no lower than three (3) feet above the Base Flood Elevation and be securely anchored to an adequately anchored foundation system to resist flotation, collapse, and movement.
 - c. Manufactured Homes as permitted in section 14-18(3)(a) shall be anchored to prevent flotation, collapse or lateral movement. For the purpose of this requirement, Manufactured Homes must be anchored to resist flotation, collapse or lateral movement in accordance with section 40-29-10 of the South Carolina Manufactured Housing Board Regulations. Additionally, the chassis must be elevated a minimum of three (3) feet above the Base Flood Elevation the chassis shall be supported by reinforced piers or other foundation elements at least equivalent strength.
 - d. An evacuation plan must be developed for evacuation of all residents of all Substantially Improved or Substantially Damaged Existing Manufactured Home Park or subdivisions located within Flood-prone areas. This plan shall be filed with and approved by the local floodplain administrator and the local Emergency Preparedness Coordinator.
- (4) *Elevated Structures.* New Construction, Addition and/or Substantial Improvements of elevated Structures that include limited enclosures (allowed only in AE flood zones) in an area below the Lowest Floor that are useable solely for parking of vehicles, building access, or Limited Storage Area other than a Basement, and which are subject to flooding shall be designed to preclude finished space and designed to automatically equalize hydrostatic Flood forces on exterior walls by allowing for the entry and exit of floodwaters.
 - a. Designs for complying with this requirement must be certified by a professional engineer or architect and meet or exceed the following minimum criteria:

1. Provide a minimum of two (2) openings on different walls having a total net area of not less than one (1) square inch for every square foot of enclosed area subject to flooding;
 2. The bottom of all openings shall be no higher than one (1) foot above the higher of the interior or exterior grade immediately under the opening,
 3. Only the portion of openings that are below the Base Flood Elevation (BFE) can be counted towards the required net open area.
 4. Openings may be equipped with screens, louvers, valves, or other coverings or devices provided they permit the automatic flow of floodwaters in both directions;
 5. Fill placed around foundation walls must be graded so that the grade inside the enclosed area is equal to or higher than the adjacent grade outside the Structure on at least one (1) side of the Structure.
- b. Enclosures below Lowest Floor in AE zones:
1. Access to the enclosed area shall be the minimum necessary to allow for parking of vehicles (garage door) or Limited Storage Area of maintenance equipment used in connection with the premises (standard exterior door) or entry to the living area (stairway or elevator). Total enclosed area shall not exceed two hundred ninety (290) square feet. No other enclosures shall be permitted below the required Base Flood Elevation.
 2. The interior portion of such enclosed area shall not be finished or partitioned or finished into separate rooms, must be void of utilities except for essential lighting as required for safety, and cannot be temperature controlled.
 3. One (1) wet location switch and/or outlet connected to a ground fault circuit interrupt breaker may be installed below the required Lowest Floor elevation specified in subsections 14-18(1), (2) and (3).
 4. All construction materials below the required Lowest Floor elevation specified in subsections 14-18(1), (2), and (3) shall be of Flood-Resistant Materials.
 5. Enclosures of any kind shall be prohibited in the VE and Coastal A zones except for elevators and open stairways.
- c. *Hazardous velocities.* Hydrodynamic pressure must be considered in the design of any foundation system where velocity waters or the potential for debris flow exists. Therefore, solid foundation walls shall not be permitted.
- (5) *Accessory structures.* Any detached Accessory Structure used only for parking of vehicles and Limited Storage Area are permitted at grade if the following criteria is met:
- a. In SFHAs other than Coastal High Hazard Areas (Zone AE), they are not larger than one (1) story and 600 square feet in area. Walls must have openings in compliance with section 14-18(4)a. b. Accessory Structures shall be constructed of Flood-Resistant Material below the Base Flood Elevation and designed to have low Flood damage potential in accordance with Technical Bulletin 2, Flood Damage Resistant Material Requirements;
 - c. Accessory Structures shall be constructed and placed on the building site so as to offer the minimum resistance to the flow of floodwaters;
 - d. Accessory Structures shall be firmly anchored to prevent flotation, collapse, or lateral movement of the Structure;
 - e. Service facilities such as electrical, mechanical and utility equipment shall be installed in accordance with subsection 14-17(5);
 - f. Accessory Structures shall comply with Town zoning regulations; and.

- g. Accessory Structures shall be prohibited in the VE and Coastal A zone.

Exception: Swimming pools shall be allowed meeting section 14-17(22) of this chapter.

- (6) *Fill.* Fill and raised slab construction is discouraged because Flood storage capacity is removed from floodplains. Elevating Structures by other methods should be utilized. An applicant shall prove through engineering analysis that fill is the only alternative to raising the Structure to at least three (3) feet above the Base Flood Elevation, and that the amount of fill used will not affect the Flood storage capacity or adversely affect adjacent properties. Slabs of any kind, including raised slab foundations, or stem walls shall not be utilized in the SFHA. Piers, pilings, or flow-through crawlspaces shall be utilized. The following provisions shall apply to any fill placed in the SFHA:

- a. Fill may not be placed in tidal or non-tidal wetlands without the required state and federal permits;
- b. Fill must consist of soil and rock materials only. Dredged material may be used as fill only upon certification of suitability by a registered professional geotechnical engineer. Landfills, rubble fills, dumps and sanitary fills are not permitted in the floodplain;
- c. Fill used to support Structures must comply with ASTM Standard D-698, and its suitability to support Structures must be certified by a registered professional engineer for "designed and compacted fill" that meets the criteria of (1) Section 1803.5.8 and Section 1804.5 of the International Building Code, (2) Section 2.4 of ASCE 24, or (3) their equivalent); and must be on fill that has appropriate protection from erosion and scour.
- d. Fill slopes shall be no greater than two (2) horizontal to one (1) vertical. Flatter slopes may be required where velocities may result in erosion;
- e. The use of fill shall not increase Flooding or cause drainage problems on neighboring properties;
- f. Fill may not be used for Structural support in the Coastal High Hazard Areas (VE).

(7) *Elevators*

- a. Install a float switch system or another system that provides the same level of safety necessary for all elevators where there is a potential for the elevator cab to descend below the BFE during a Flood per FEMA's Technical Bulletin 4 Elevator Installation.
- b. All equipment that may have to be installed below the BFE such as counterweight roller guides, compensation cable and pulleys, and oil buffers for traction elevators and the jack assembly for a hydraulic elevator must be constructed using Flood-Resistant Materials where possible per FEMA's Technical Bulletin 4 Elevator Installation.

- (8) Any unauthorized or construction inconsistent with plans approved by the Town will be required to return the area to original conditions. This requirement includes existing properties.

Sec. 14-19. - Standards for areas outside of the Special Flood Hazard Area (SFHA).

Other areas of the Town are subject to periodic inundation of Flood waters due to acts of nature, stormwater drainage and other issues. These properties, although outside of the SFHA, need to be protected. The Town wishes to minimize any potential ~~lost~~ **loss** due to periodic flooding by enforcing certain requirements within the 100-year and 500-year Flood zones. These Flood zones have no Base Flood Elevation data therefore the following requirements are to be enforced on all New Construction and Additions:

- (1) Minimum finished floor elevation.
 - a. All new non-commercial Structures, not located in a SFHA, shall have the Lowest Floor and all mechanical or electrical equipment, such as compressors, air conditioning units, etc., elevated no less than eighteen (18) inches above the Highest Adjacent Grade of the lot. Final site grading shall ensure that ponding of stormwater will not occur beneath the

Structure, or nearer than three (3) feet from the Structure's perimeter or any mechanical or electrical equipment.

- b. All new commercial structures, not located in a SFHA, shall have the Lowest Floor and all mechanical or electrical equipment, such as compressors, air conditioning units, etc., elevated not less than eighteen (18) inches above the centerline of the road. Final site grading shall ensure that ponding of stormwater will not occur beneath the Structure, or nearer than three (3) feet from the Structure's perimeter or any mechanical or electrical equipment.
 - c. Non-commercial developable lots outside of the SFHA shall have an average grade of all adjacent lots. A foundation/current conditions survey shall be provided and approved prior to the foundation being poured or piers being filled prior to additional inspections being performed. Adjacent lot grades shall be measured at a minimum of twenty (20) feet into all adjacent lots.
- (2) Slab on grade foundations shall be prohibited.
 - (3) Enclosed crawl space construction must be designed and certified by a professional engineer to meet the following minimum criteria:
 - a. Provide a minimum of two (2) Flood Vents on different walls having a total net area of not less than one (1) square inch for every square foot of enclosed area subject to flooding;
 - b. The bottom of all Flood Vents shall be no higher than one (1) foot above the higher of the interior or exterior grade immediately under the opening,
 - c. Flood Vents may be equipped with screens, louvers, valves, or other coverings or devices provided they permit the automatic flow of floodwaters in both directions.
 - (4) The installation of outdoor faucets for shower heads, hoses, etc., are permitted as long as cutoff devices and backflow devices are installed to prevent contamination of the service components and thereby minimize any flood damages to a structure and contents;
 - (5) Gas/propane containers shall be adequately anchored to prevent floatation, collapse, or lateral movement. . Horizontal propane tanks shall install four (4) ground anchors connected across the top of the tank with metal straps. Vertical propane tanks shall be installed with two ground anchors, each anchor placed on opposite sides of the vertical tank. A strap shall be attached from each anchor to the collar secured around the top of the tank. An additional metal strap shall be connected from one anchor to the other through the tank base. Ground anchors, straps, and connecting hardware must be corrosion – resistant.

Sec. 14-20. - Standards for subdivision proposals and other developments.

All subdivision proposals and other proposed new development shall be consistent with the need to minimize Flood damage and are subject to all applicable standards in these regulations.

- (1) All subdivision proposals and other proposed new development shall have public utilities and facilities such as sewer, gas, electrical, and water systems located and constructed to minimize Flood damage. An access road at or above the Base Flood Elevation shall be provided to allow emergency access during Flood conditions.
- (2) All subdivision proposals and other new development shall have adequate drainage provided to reduce exposure to Flood hazards.
- (3) Base Flood Elevation data shall be provided for all subdivision proposals of fifty (50) lots or more than five (5) acres or greater.
- (4) All residential subdivision proposals having fifty (50) lots or more shall be required to provide an approved evacuation plan.

Sec. 14-21. - Reserved.

Sec. 14-22. - Coastal High Hazard Areas (VE and Coastal A zones).

Located within the SFHA established in section 14-4, are areas designated Coastal High Hazard Areas. These areas have special Flood hazards associated with wave wash. The following provisions shall apply within all such areas in addition to those requirements set forth in section 14-17 of this chapter:

- (1) All New Construction, Addition and Substantial Improvements shall be located landward of the reach of mean high tide, first line of Stable Natural Vegetation and comply with all applicable Department of Health and Environmental Control (DHEC) Ocean and Coastal Resource Management (OCRM) setback requirements.
- (2) All Structures shall be elevated so that the bottom of the lowest supporting horizontal member (excluding pilings or columns) is located no lower than three (3) feet above the Base Flood Elevation level, with all space below the lowest supporting member open so as not to impede the flow of water.
- (3) All Structures shall be securely anchored on pilings or columns, extending vertically below a grade of sufficient depth and the zone of potential scour, and securely anchored to the subsoil strata.
- (4) All pilings and columns and the attached structures shall be anchored to resist flotation, collapse, lateral movement and scour due to the effect of wind and water loads acting simultaneously on all building components.
- (5) A registered professional engineer shall certify that the design, specifications and plans for construction are in compliance with the provisions contained in sections 14-22(3), (4), (6), (8), (9), (12), (13), (14) and (15) of this chapter.
- (6) There shall be no fill material used as structural support. Non-compacted fill may be used around the perimeter of a Structure for landscaping/aesthetic purposes, provided the fill will wash out from storm surge, thereby rendering the Structure free of obstruction prior to generating excessive loading forces, ramping effects, or wave deflection. Only beach-compatible sand may be used. Parking slabs under Structures shall be designed without grade beams, a maximum of four (4) inches in thickness, designed to break apart during storm surge scouring. The local floodplain administrator shall approve design plans for landscaping/aesthetic fill only after the applicant has provided analysis by an engineer and/or soil scientist, which demonstrates that the following factors have been fully considered:
 - a. Particle composition of fill material does not have a tendency for excessive natural compaction;
 - b. Volume and distribution of fill will not cause wave deflection to adjacent properties; and
 - c. Slope of fill will not cause wave run-up or ramping.
- (7) There shall be no alteration of sand dunes, which would increase potential Flood damage.
- (8) Any alteration, repair, reconstruction, or improvement to a Structure shall not enclose the space below the Lowest Floor.
- (9) No Manufactured Homes shall be permitted.
- (10) Recreational Vehicles shall not be permitted in Coastal High Hazard Areas.
- (11) Accessory Structures shall be prohibited.
- (12) Access stairs attached to or beneath an Elevated Structure must be constructed of Flood Resistant Materials, and must be constructed as open staircases so they do not block flow under the Structure in accordance with section 14-22(2)
- (13) Decks

- a. If the deck is structurally attached to a Structure then the bottom of the lowest horizontal member must be at or above the elevation of the Structures lowest horizontal member.
 - b. If the deck is to be built below the BFE then it must be structurally independent of the main Structure and must not cause an obstruction.
 - c. If an at-grade, structurally independent deck is proposed then a design professional must evaluate the design to determine if it will adversely affect the Structure and nearby Structures.
- (14) Electrical, ventilation, plumbing, heating and air conditioning equipment (including ductwork), and other service facilities shall be designed and/or located at a minimum three (3) feet above the lowest horizontal member so as to prevent water from entering or accumulating within the components during conditions of a Base Flood event. This requirement does not preclude the installation of outdoor faucets for showerheads, sinks, hoses, etc., as long as cut-off devices and backflow devices are installed to prevent contamination to the service components and thereby minimize any flood damage to the building.
- (15) Documentation from a professional engineer must be presented to the Town stating the slab placed under the Structure is not connected to the foundation.
- (16) Enclosures of any kind including but not limited to storage, breakaway walls (including non-supporting), open lattice work or insect screening shall be prohibited below the Base Flood Elevation and required Freeboard. Elevators and open stairways shall be permitted provided they meet the minimum requirements of the NFIP.
- (17) Elevators shall be permitted provided they meet the minimum requirements of the NFIP Technical Bulletin 4 / June 2019
- (18) One (1) wet location switch and/or outlet connected to a ground fault circuit interrupt breaker may be installed below the required lowest floor elevation in residential and commercial construction.

ARTICLE II. - VARIANCE PROCEDURES ^[3]

Sec. 14-23. - Establishment of appeals board.

The Construction Board of Appeals as established by the Town shall hear and decide requests for variances from the requirements of this chapter.

Sec. 14-24. - Right to appeal.

Any person aggrieved by the decision of the Construction Board of Appeals or any taxpayer may Appeal such decision to court.

Sec. 14-25. - Historic Structures.

Variances may be issued for the repair or rehabilitation of Historic Structures upon the determination that the proposed repair or rehabilitation will not preclude the Structure's continued designation as a Historic Structure, and the variance is the minimum necessary to preserve the historic character and design of the structure.

Sec. 14-26 - Functionally Dependent Uses

Variances may be issued for Development necessary for the conduct of a Functionally Dependent Use, provided the criteria of this chapter is met, no reasonable alternative exist, and the Development is protected by methods that minimize Flood damage and create no additional threat to public safety.

Sec. 14-27 - Accessory Structures and Agricultural Structures]

A variance may be issued for the construction or Substantial Improvement of Accessory Structures and Agricultural Structures provided ~~the~~ that the proposed construction or Substantial Improvement represents a minimal investment and has low Flood damage potential based on an amount of physical damage, contents damage, and loss of function.

Sec. 14-28. - Considerations.

In passing upon such applications, the Construction Board of Appeals shall consider all technical evaluations, all relevant factors, all standards specified in other sections of the chapter and:

- (1) The danger that materials may be swept onto other lands to the injury of others;
- (2) The danger to life and property due to flooding or erosion damage, and the safety of access to the property in times of Flood for ordinary and emergency vehicles;
- (3) The susceptibility of the proposed facility and its contents to Flood damage and the effect of such damage to the individual owner;
- (4) The importance of the services provided by the proposed facility to the community;
- (5) The necessity to the facility of a waterfront location, where applicable;
- (6) The availability of alternative locations, not subject to flooding or erosion damage, for the proposed use;
- (7) The compatibility of the proposed use with existing and anticipated development, and the relationship of the proposed use to the comprehensive plan and floodplain management program for that area;
- (8) The expected heights, velocity, duration, rate of rise, and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site;
- (9) The costs of providing governmental services during and after Flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical and water systems, and streets and bridges; and
- (10) Agricultural Structures must be located in wide, expansive floodplain areas, where no other alternative location for the Agricultural Structure exists. The applicant must demonstrate that the entire farm acreage, consisting of a contiguous parcel of land on which the Structure is to be located, must be in the SFHA and no other alternative locations for the Structure are available.

Sec. 14-29. - Findings.

Findings listed above shall be submitted to the Construction Board of Appeals, in writing, and included in the application for a variance. Additionally, comments from the Department of Natural Resources, Land, Water and Conservation Division, State Coordinator's Office, must be taken into account and included in the permit file.

Sec. 14-30. - Conditions.

Upon consideration of the factors listed above and the purposes of this chapter, the Construction Board of Appeal may attach such conditions to the granting of variances as it deems necessary to further the purposes of this chapter. The following conditions shall apply to all variances:

- (1) Variances may not be issued when the variance will make the Structure in violation of other federal, state, or local laws, regulations or ordinances.
- (2) Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the Flood hazard, to afford relief.
- (3) Variances shall only be issued upon a showing of good and sufficient cause, a determination that failure to grant the variance would result in exceptional hardship, and a determination that the granting of a variance will not result in increased Flood heights, additional threats to public safety, extraordinary public expense, create a nuisance, cause fraud on or victimization of the public, or conflict with existing laws or ordinances.
- (4) Any applicant to whom a variance is granted shall be given written notice specifying the difference between the Base Flood Elevation and the elevation to which the Structure is to be

built and a written statement that the cost of Flood insurance will be commensurate with the increased risk. Such notification shall be maintained with a record of all variance actions.

- (5) The local floodplain administrator shall maintain the records of all appeal actions and report any variances to FEMA upon request.
- (6) Variances shall not be issued for any Structure or development begun without proper permits that is not in compliance with the provisions of this chapter. Violations shall be corrected in accordance with subsection 14-16(5) of this chapter.

Sec. 14-31. - Effect on rights and liabilities under the existing flood damage prevention ordinance.

This chapter in part comes forward by reenactment of some of the provisions of the Flood damage prevention ordinance enacted November 10, 2014, as amended, and it is not the intention to repeal but rather reenact and continue to enforce without interruption of such existing provisions, so that all rights and liabilities that have accrued thereunder are reserved and may be enforced. The enactment of this chapter shall not affect any action, suit, or proceeding instituted or pending. All provisions of the Flood damage prevention ordinance of the Town enacted on November 10, 2014, as amended, which are not reenacted herein, are repealed.

Sec. 14-32. - Effect upon outstanding building permits.

Nothing herein contained shall require any change in the plans, construction, size or designated use of any Structure or part thereof for which a building permit has been granted by the Town before the time of passage of this chapter, or any modification thereof; provided, however, that when construction is not begun under such outstanding permit within a period of sixty (60) days subsequent to the passage of this chapter or any modification thereof, construction or use shall be in conformity with the provisions of this chapter.

Sec. 14-33. - Effective date.

This chapter shall become effective upon adoption.

Secs. 14-34—14-45. - Reserved.



SEVERABILITY. If any provision, clause, sentence, or paragraph of this ordinance or the application thereof to any person or circumstances shall be held invalid, that invalidity shall not affect the other provisions of this article, which can be given effect without the invalid provision or application, and to this end the provisions of this article are declared to be severable.

EFFECT OF SECTION HEADINGS. The headings or titles of the sections hereof shall be solely for convenience of reference and shall not affect the meaning, construction, interpretation or effect of this ordinance.

REPEAL AND EFFECTIVE DATE. All ordinances or parts of ordinances inconsistent with this ordinance are hereby repealed. This ordinance shall take effect immediately upon second reading by the Mayor and Town Council of the Town of Surfside Beach.

BE IT ORDERED AND ORDAINED by the Mayor and Town Council of the Town of Surfside Beach, South Carolina, in assembly and by the authority thereof, this _____ day of _____ 2021.

Surfside Beach Town Council

Bob Hellyer, Mayor

Debbie Scoles, Pro Tempore

Bruce H. Dietrich, Town Council

Michael Drake, Town Council

Paul Holder, Town Council

Cindy Keating, Town Council

David Pellegrino, Town Council

Attest: _____
Sheri Medina, Town Clerk